


NO: CE-1003/1

1. Unique identification code of the product: **Opti-Step™ 1003**
2. Intended use: **Underlays for laminate floor**
3. Manufacturer: **Sealed Air Svenska AB, Box 146, 578 23 Aneby, Sweden**
4. System of AVCP: **System 4**
5. Harmonized standard: **EN 16354:2018**
6. Notified Body: **N/A**
7. Declared performance:


Physical Properties	Test Method	Unit	Value	Tolerances
Nominal Density	ISO 845	Kg/m <sup>3</sup>	30	± 15%
Area Weight (AW)	EN 1923	gr/m <sup>2</sup>	60	± 15%
Thickness (t)	EN 823 + A.3.1	mm	2	± 15%
Length (l)	EN 822 + A.3.3	m	15-150	-0%, +5%
Width (w)	EN 822 + A.3.3	mm	1000-1500	-1%, +2.5%
Compression Strength (CS)	EN826 + A.3.7.	kPa	>20	-
Compressive Creep (CC)	EN 1606 + A.3.8	kPa	>2	-
Punctual Conformability (PC)	EN 869 + A.3.6	mm	1,3	-
Resistance to Impact by Large Diameter Ball (RLB)	EN 13329	mm	800	-
Thermal Resistance (R)	EN 12667	m <sup>2</sup> K/W	0,04	-
Moisture Resistance (SD)	EN 12086, Method A	m	>8	-
Impact Sound Reduction (IS)	EN ISO 10140-3 EN ISO 717-2	ΔLw in dB	≥19	-
Emission of Formaldehyde and VOC	EN ISO 16000-9		Class A+	-
Alkaline Resistance (AR)	EN 14909	Pass or Fail	Pass	-

The performance of the product is in conformity with the declared performance outlined above.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

  
 .....  
**Thomas Piper, Plant Manager**

Date: 19.08.19

 Produced in Sweden